

**DISPLAY**

Display Size (in.):	27
Viewable Area (in.):	27
Panel Type:	IPS Technology
Resolution:	3840 x 2160
Resolution Type:	UHD (Ultra HD)
Static Contrast Ratio:	2,000:1 (typ)
Dynamic Contrast Ratio:	20M:1
High Dynamic Range:	VESA HDR400
Light Source:	LED
Brightness:	400 cd/m <sup>2</sup> (typ)
Colors:	1.07B
Color Space Support:	10 bit (8 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	5ms
Response Time (GTG w/OD):	5ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	60
Low Blue Light:	TUV Low Blue Light (Hardware solution)
Flicker-Free:	TUV Flicker Free

Color Gamut:	Adobe RGB: 99% size / 89% coverage (Typ) DCI-P3: 99% size / 98% (CIE 1976) coverage (Typ) EBU: 132% size / 100% coverage (Typ) REC709: 134% size / 100% coverage (Typ) SMPTE-C: 144% size / 100% coverage (Typ) NTSC: 95% size (Typ) sRGB: 134% size / 100% coverage (Typ)
--------------	--

Pixel Size:	0.155 mm (H) x 0.155 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

**COMPATIBILITY**

PC Resolution (max):	3840x2160
Mac® Resolution (max):	3840x2160
PC Operating System:	Windows 11 certified; macOS tested
Mac® Resolution (min):	3840x2160

**CONNECTOR**

USB 3.2 Type A Down Stream:	3
USB 3.2 Type C Up Stream:	1
Micro USB:	1
Thunderbolt™ 4 Up Stream:	1 (100W power charger)
Thunderbolt™ 4 Down Stream:	1 (15W power charger)
3.5mm Audio Out:	1
HDMI 2.1:	2
DisplayPort:	1
Power in:	DC Socket (4 Pin)
Ethernet LAN (RJ45):	1

**AUDIO**

Internal Speakers:	3Watts x2
--------------------	-----------

**POWER**

Eco Mode (Conserve):	21.5W
Eco Mode (optimized):	25.5W
Consumption (typical):	29W
Consumption (max):	32W
Voltage:	AC 100-240V
Stand-by:	0.5W
Power Supply:	External Power Adaptor

**ADDITIONAL HARDWARE**

Kensington Lock Slot:	1
Cable Organization:	Yes

**CONTROLS**

Physical Controls:	Joystick key: Up, Right, Down, Left, Center; Power
On Screen Display:	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

**WALL MOUNT**

VESA Compatible:	100 x 100 mm
------------------	--------------

**INPUT SIGNAL**

Frequency Horizontal:	30 ~ 150KHz
Frequency Vertical:	24 ~ 75Hz

**VIDEO INPUT**

Digital Sync:	PCI-E - DisplayPort (v1.4), TMDS compatible - HDMI (v2.1), PCI-E - TBT4
---------------	---

**ERGONOMICS**

Height Adjust (mm):	120
Swivel:	120°
Tilt (Forward/Back):	-3° / 22°
Pivot (Right/Left):	90° / 90°

**WEIGHT (IMPERIAL)**

Net (lbs):	16.8
Net Without Stand (lbs):	9.3
Gross (lbs):	28.9

**WEIGHT (METRIC)**

Net (kg):	7.6
Net Without Stand (kg):	4.2
Gross (kg):	13.1

**DIMENSIONS (IMPERIAL) (WXHxD)**

Packaging (in.):	28.3 x 20.3 x 9
Physical (in.):	24.16 x 17.73~22.46 x 9.21
Physical Without Stand (in.):	24.16 x 14.32 x 2.2

**DIMENSIONS (METRIC) (WXHxD)**

Packaging (mm):	720 x 515 x 228
Physical (mm):	613.7 x 450.36~570.36 x 234
Physical Without Stand (mm):	613.7 x 363.85 x 55.8

**GENERAL**

Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCan, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO
--------------	---

PACKAGE CONTENTS:	VP2776T-4K x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, HDMI Cable (v2.1; Male-Male) x1, TBT4 Cable (Male-Male) x1, USB Type-C to Type-A 3.2 Gen2 Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
-------------------	--

Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
-------------------	--

Warranty:	*Warranty offered may differ from market to market
-----------	--

Power Management:	Energy Star standards, EPEAT
-------------------	------------------------------

